

RZR XP 4 1000 Premium Matte Titanium Onyx Black



Key Specifications

114
HP

64"
WIDTH

14.5"
GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance True On-Demand AWD/2WD
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke DOHC Twin Cylinder
Fuel System/Battery	Electronic Fuel Injection
Horsepower	114 HP
Transmission/Final Drive	Automatic PVT P/R/N/L/H

DIMENSIONS

Bed Box Dimensions (L x W x H)	28 x 22 x 7 in (72.0 x 57.0 x 17.8 cm)
Box Capacity	300 lb (136 kg)
Estimated Dry Weight	1,896 lbs (860 kg)
Fuel Capacity	9.5 gal (36 L)
Ground Clearance	14.5 in (36.8 cm)
Hitch Towing Rating	N/A
Overall Vehicle Size (L x W x H)	147.8 x 64 x 75 in (375.4 x 162.6 x 190.5 cm)
Payload Capacity	900 lb (408 kg)
Wheelbase	117 in (297.2 cm)

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Single Bore Rear Calipers
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Cargo System	Lock & Ride®
Doors	Front & Rear Full Doors
Electronic Power Steering	Standard with Quick Turn Rack
Hitch Type	Not Equipped
Instrumentation	PMX-2 Head Unit, AM/FM/WB tuner, compact digital media receiver, 2.7 in. full color display, TFT display delivers full viewing capabilities in full sun, Pandora control capabilities, Bluetooth audio streaming, LED button illumination, water resistant rotary encoder knob. Rockford Fosgate® Stage 1 Audio (Including 2 Front Co-axial Speakers) Dual-sweep Analog Dials w/ 4 in LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
Lighting	LED Head Lights & Tail Lights Illuminated In-Cab Controls
Other Standard Features	Color Matched Seats, Premium Paint & Graphics, Color-Matched Dash, 660-W Charging System, 6-Position Pulse Bar, Tilt Steering, Poly Sport Roof, Rockford Fosgate Stage 1® Audio & PMX Unit, Adjustable 4-Point Subzero Harnesses, Front Tow Loop, Front Bumper
RIDE COMMAND+	Available
Seat Type	Bolstered Bucket Seats with Driver & Passenger Seat Sliders and Adjustable 4-Point Subzero Harnesses *2nd Row Raised Seating*

TIRES / WHEELS

Front Tires	Trail Master X/T 2.0, 30 x 10-14 Radial Tire
Rear Tires	Trail Master X/T 2.0, 30 x 10-14 Radial Tire
Wheels	Cast Aluminum

SUSPENSION

Electronic Suspension Control System	Not Equipped
Front Shocks	2" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers
Front Suspension	Dual A-Arm with Stabilizer Bar and 20.5 in (52.07 cm) *Usable Travel, 16 in (40.6 cm) of Wheel Travel
Rear Shocks	2.5" Walker Evans® Needle Shocks with 16-Position Adjustable Clickers
Rear Suspension	Trailing Arm with Stabilizer Bar and 20.5 in (52.07 cm) Usable Travel*, 18 in (45.7 cm) of Wheel Travel